

NUMBER		NOT REQ'D	NOT DONE	SATISFIED	Underground Retention			
					REVIEW #			
					BY		DATE	
	ITEMS				Location in Standards			

1	½ Flush surface retention then into a drywell	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
2	Dewater within 36 hours	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
3	Ok Materials – perforated, storm tech, con arc, HDPE (NO CMP)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
4		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
5		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
6		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
7		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
8		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
9		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
10		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	